



YORK® LX SERIES RESIDENTIAL PACKAGE EQUIPMENT

The YORK® quality advantage. YORK® LX Series Residential Package Equipment delivers advanced efficiency with industry-leading reliability. Models featuring 16 SEER ratings are up to 38% more efficient than older units, and over 250,000 hours of research and testing ensure long-term durability. Installation and maintenance have also been made easier than ever, to maximize profitability with every job.

Faster installation and service:

Compressor, refrigeration controls and blower are all accessible through front access, while the evaporator coil slides out for easy cleaning. Convenient gas and electric hookups make it easy to connect the unit to power sources.

Proven condenser coil:

Copper tube/aluminum fin condenser coils combine outstanding heat transfer rate with long-term reliability.

Reduced complexity:

Standardized design ensures consistent performance and reliability across the product range and reduces replacement parts for servicing.



Affordable efficiency:

16 SEER package equipment qualifies as ENERGY STAR® products, meets U.S. Department of Energy standards and is up to 38% more efficient than older, 10 SEER units.

Gas heat exchanger with lifetime warranty:

Stainless steel tubular gas heat exchanger is proven by over 1,000,000 lab-test cycles and and gas heat models come with a standard, lifetime limited warranty.

Maintain appearance:

Powder-coat finish with 1,000-hour salt-spray rating ensures the exterior finish provides outstanding corrosion resistance and superior appearance in harsh conditions.

Strong base rails:

Fits on roof frames or slabs with no problem, and through gates and onto service trucks for faster installation time.



YORK® residential products carry the **Good Housekeeping Seal of Approval.**



16 SEER package equipment qualifies as **ENERGY STAR®** products.



LX Series Residential Package Equipment is designed, engineered and assembled in the United States, where we can closely monitor and improve processes that directly affect quality. It's this commitment to excellence that allows us to offer outstanding warranties, meet the highest industry standards, and deliver energy-saving comfort that lasts a lifetime. That's why, when it comes to home comfort, your confidence is our commitment.

PCE6 Electric/Electric Packaged Units 208/230-1-60 

| MODEL | TONS | SEER | EER | COOLING BTUH (NOMINAL) | HEATING BTUH (NOMINAL) | DIMENSIONS (INCHES) | | | WEIGHT (LBS.) |
|-----------|------|------|------|------------------------|------------------------|---------------------|--------|--------|---------------|
| | | | | | | LENGTH | WIDTH | HEIGHT | |
| PCE6A2421 | 2.0 | 16.0 | 12.5 | 24,000 | Up to 13kW | 51-1/4 | 35-3/4 | 47 | 343 |
| PCE6A3021 | 2.5 | 16.0 | 12.5 | 30,000 | Up to 15kW | 51-1/4 | 35-3/4 | 47 | 389 |
| PCE6B3621 | 3.0 | 16.0 | 12.5 | 36,000 | Up to 15kW | 51-1/4 | 45-3/4 | 49 | 460 |
| PCE6B4221 | 3.5 | 16.0 | 12.5 | 42,000 | Up to 20kW | 51-1/4 | 45-3/4 | 49 | 466 |
| PCE6B4821 | 4.0 | 16.0 | 12.5 | 48,000 | Up to 25kW | 51-1/4 | 45-3/4 | 53 | 483 |
| PCE6B6021 | 5.0 | 16.0 | 12.0 | 60,000 | Up to 25kW | 51-1/4 | 45-3/4 | 55 | 500 |

PHE6* Electric/Electric Packaged Heat Pumps 208/230-1-60 

| MODEL | TONS | SEER | EER | HSPF | COOLING BTUH (NOMINAL) | HEATING BTUH (NOMINAL) | DIMENSIONS (INCHES) | | | WEIGHT (LBS.) |
|-----------|------|------|------|------|------------------------|------------------------|---------------------|--------|--------|---------------|
| | | | | | | | LENGTH | WIDTH | HEIGHT | |
| PHE6A2421 | 2.0 | 16.0 | 12.5 | 8.2 | 24,000 | Up to 13kW | 51-1/4 | 35-3/4 | 47 | 377 |
| PHE6A3021 | 2.5 | 16.0 | 12.5 | 8.2 | 30,000 | Up to 15kW | 51-1/4 | 35-3/4 | 47 | 392 |
| PHE6B3621 | 3.0 | 16.0 | 12.5 | 8.2 | 36,000 | Up to 15kW | 51-1/4 | 45-3/4 | 49 | 448 |
| PHE6B4221 | 3.5 | 16.0 | 12.5 | 8.2 | 42,000 | Up to 20kW | 51-1/4 | 45-3/4 | 49 | 471 |
| PHE6B4821 | 4.0 | 16.0 | 12.5 | 8.2 | 48,000 | Up to 25kW | 51-1/4 | 45-3/4 | 53 | 496 |
| PHE6B6021 | 5.0 | 16.0 | 12.5 | 8.2 | 60,000 | Up to 25kW | 51-1/4 | 45-3/4 | 55 | 523 |

*Up to 25kW Supplemental Electric Heat

PCG6 Electric Cooling/Gas Heating Packaged Units 208/230-1-60 

| MODEL | TONS | SEER | EER | AFUE | COOLING BTUH (NOMINAL) | HEATING BTUH (NOMINAL) | DIMENSIONS (INCHES) | | | WEIGHT (LBS.) |
|---------------|------|------|------|------|------------------------|------------------------|---------------------|--------|--------|---------------|
| | | | | | | | LENGTH | WIDTH | HEIGHT | |
| PCG6A240502X1 | 2.0 | 16.0 | 12.5 | 81% | 24,000 | 50,000 | 51-1/4 | 35-3/4 | 47 | 367 |
| PCG6A240752X1 | 2.0 | 16.0 | 12.5 | 81% | 24,000 | 75,000 | 51-1/4 | 35-3/4 | 47 | 377 |
| PCG6A300502X1 | 2.5 | 16.0 | 12.5 | 81% | 30,000 | 50,000 | 51-1/4 | 35-3/4 | 47 | 412 |
| PCG6A300752X1 | 2.5 | 16.0 | 12.5 | 81% | 30,000 | 75,000 | 51-1/4 | 35-3/4 | 47 | 416 |
| PCG6B360652X1 | 3.0 | 16.0 | 12.5 | 81% | 36,000 | 65,000 | 51-1/4 | 45-3/4 | 49 | 461 |
| PCG6B361002X1 | 3.0 | 16.0 | 12.5 | 81% | 36,000 | 100,000 | 51-1/4 | 45-3/4 | 49 | 468 |
| PCG6B420652X1 | 3.5 | 16.0 | 12.5 | 81% | 42,000 | 65,000 | 51-1/4 | 45-3/4 | 49 | 495 |
| PCG6B421002X1 | 3.5 | 16.0 | 12.5 | 81% | 42,000 | 100,000 | 51-1/4 | 45-3/4 | 49 | 497 |
| PCG6B480652X1 | 4.0 | 16.0 | 12.5 | 81% | 48,000 | 65,000 | 51-1/4 | 45-3/4 | 53 | 515 |
| PCG6B481002X1 | 4.0 | 16.0 | 12.5 | 81% | 48,000 | 100,000 | 51-1/4 | 45-3/4 | 53 | 523 |
| PCG6B481252X1 | 4.0 | 16.0 | 12.5 | 81% | 48,000 | 125,000 | 51-1/4 | 45-3/4 | 53 | 528 |
| PCG6B600652X1 | 5.0 | 16.0 | 12.0 | 81% | 60,000 | 65,000 | 51-1/4 | 45-3/4 | 55 | 532 |
| PCG6B601002X1 | 5.0 | 16.0 | 12.0 | 81% | 60,000 | 100,000 | 51-1/4 | 45-3/4 | 55 | 536 |
| PCG6B601252X1 | 5.0 | 16.0 | 12.0 | 81% | 60,000 | 125,000 | 51-1/4 | 45-3/4 | 55 | 543 |

Learn more at YORK.com/LXSeries



The YORK brand of Johnson Controls, Inc. ©2016 Johnson Controls, Inc.
5005 York Drive, Norman, OK 73069 www.YORK.com Subject to change without notice.
PUBL-8336-B-1016. Supersedes: PUBL-8336-A-1016. All rights reserved.

LX Series PCG6



Limited warranties for Electric/Gas models PCG6: 10-year compressor, 10-year parts and lifetime heat exchanger if registered within 90 days of installation.



Otherwise warranty reverts to the standard 20-year heat exchanger warranty (1 phase). 20-year heat exchanger limited warranty in commercial applications.

LX Series PCE6 and PHE6



PCE6 and PHE6 models: 10-year compressor, 10-year parts and lifetime heat exchanger if registered within 90 days of installation. Otherwise, warranty reverts to the standard 20-year heat exchanger warranty (1 phase).



1-year labor limited warranty: if your LX Series Residential Package Equipment is delivered and does not function, repairs and labor time performed are covered at no charge.

